



DESKTOP COLOR PRINTER

Designed with Speed and Flexibility in Mind

The MX-C507P desktop color printer delivers crisp, high-quality output with exceptional ease of use. This compact printer provides customers with an intuitive user experience and the confidence of knowing their jobs will come out right the first time, every time. Packed with robust technology and features typically found on multifunction printers, the MX-C507P will give customers the confidence to print any size job from their workplace or home office.

Key Features

- Ease of Use 4.3" (diagonal) touchscreen display offers a user-friendly graphical interface and provides quick access
 to print settings, a user guide, print preview and more.
- Productivity Produces high quality, professional output at up to 50 pages per minute, plus available wireless
 connectivity enables easy access from mobile devices such as notebook computers, tablets and smartphones.
- Workspace Friendly Integrates seamlessly with today's complex network environments and supports popular cloud services and mobile technologies.





Standard desktop configuration shown.



Easy-to-use 4.3" touchscreen with tablet style menu.



Front USB port for easy direct printing from memory devices.

A compact design with advanced workflow features for virtually any size office.

- Productive printing speeds of up to 50 pages per minute.
- Intuitive 4.3" (diagonal) touchscreen offers print preview menu to ensure your documents are printed with precision.
- Supports letter and legal size paper as well as envelopes and labels through the standard paper drawer and bypass tray.
- Compact design easily fits into small spaces in desktop or console configurations.

- Offers up to **five paper sources** with available 2,300-sheet maximum paper capacity.
- Supports popular mobile technologies, enabling users to easily print files from smartphones, tablets and even notebook computers.
- Supports printing from Microsoft® Word, Excel®, or PowerPoint® directly from a mobile device, USB drive, or file server.
- Convenient front-facing USB port provides easy access for direct printing from flash drives and thumb drives.
- True 1,200 x 1,200 dpi resolution produces razor sharp documents.
- Standard PCL® 6 and PostScript®3™ compatible printing delivers clear, crisp professional output.
- 100-sheet bypass tray for envelopes, labels and specialty media.

MX-C507P SPECIFICATIONS

| a™ compatible printing systems, 1 x 550-sheet paper drawer, 50-sheet bypass tray. Black developer is included. Desktop color printer 4.3" (diagonal) color dot matrix high-resolution touch Dutput Size Min. 5½" x 8½", Max. 8½" x 14" Print Speed 50 pm First Print Time Color: 5.5/Monochrome: 5.0 Faper Capacity Standard: 650 sheets/Maximum: 2,300 sheets Paper Feed Standard: 550-sheet paper drawer and 100-sheet bypass tray (letter/legal/statement/envelope/label size). Optional: 550-sheet paper drawer (letter/legal/statement/envelope/label size). Paper Weights Standard paper drawer and bypass tray: 16 lb. to 47 lb. bond (Plain paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design unterface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets | Main Specification | ns |
|--|---------------------------|--|
| drawer, 50-sheet bypass tray. Black developer is included. Type Desktop color printer 4.3" (diagonal) color dot matrix high-resolution touch Dutput Size Min. 5½" x 8½", Max. 8½" x 14" Print Speed 50 ppm First Print Time (in seconds)* Paper Capacity Paper Capacity Standard: 650 sheets/Maximum: 2,300 sheets Paper Feed Standard: 550-sheet paper drawer and 100-sheet bypass tray (letter/legal/statement/envelope/label size). Optional: 550- sheet paper drawer (letter/legal/statement/envelope/ label size). Paper Weights Standard paper drawer and bypass tray: 16 lb. to 47 lb. bond Print Speed Glain paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Account Control Supports user-number authentication Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Environmental Environmental Environmental Environmental Environmental Environmental Exit Tray (Main): 300 sheets Capacity Power 0.86kW | MX-C507P | |
| Display 4.3" (diagonal) color dot matrix high-resolution touch Display 4.3" (diagonal) color dot matrix high-resolution touch Dutput Size Min. 5½" x 8½", Max. 8½" x 14" 50 ppm Color: 5.5/Monochrome: 5.0 (in seconds)* Paper Capacity Standard: 650 sheets/Maximum: 2,300 sheets Paper Feed Standard: 550-sheet paper drawer and 100-sheet bypass tray (letter/legal/statement/envelope/label size). Optional: 550-sheet paper drawer and bypass tray: 16 lb. to 47 lb. bond Resper Weights And Types Paper Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer drawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer drawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Japer Grawer and bypass tray: 16 lb. to 47 lb. bond Paper Upper Japer Japer Japer Japer Japer Japer Jape | | 3™ compatible printing systems, 1 x 550-sheet paper |
| Display 4.3" (diagonal) color dot matrix high-resolution touch Dutput Size Min. 5½" x 8½", Max. 8½" x 14" Print Speed 50 ppm Color: 5.5/Monochrome: 5.0 Standard: 650 sheets/Maximum: 2,300 sheets Paper Capacity Paper Feed Standard: 550-sheet paper drawer and 100-sheet bypass tray System (letter/legal/statement/envelope/label size). Optional: 550-sheet paper drawer (letter/legal/statement/envelope/ label size). Paper Weights and Types (Plain paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Remote access to service logs and click counts Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Standards Power 100-127V AC, 47 to 63 Hz Exit Tray (Main): 300 sheets Capacity Power 0.86kW | | drawer, 50-sheet bypass tray. Black developer is included. |
| Output Size Print Speed Print Speed First Print Time (in seconds)* Paper Capacity Praper Feed Standard: 650 sheets/Maximum: 2,300 sheets Paper Feed Standard: 550-sheet paper drawer and 100-sheet bypass tray (letter/legal/statement/envelope/label size). Optional: 550- sheet paper drawer (letter/legal/statement/envelope/ label size). Paper Weights And Types Pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Standards Power 100-127V AC, 47 to 63 Hz Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Туре | Desktop color printer |
| Print Speed First Print Time (in seconds)* Paper Capacity Paper Capacity Paper Feed Standard: 650 sheets/Maximum: 2,300 sheets Paper Feed Standard: 550-sheet paper drawer and 100-sheet bypass tray (letter/legal/statement/envelope/label size). Optional: 550- sheet paper drawer (letter/legal/statement/envelope/ label size). Paper Weights and Types (Pain paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Display | 4.3" (diagonal) color dot matrix high-resolution touch |
| Color: 5.5/Monochrome: 5.0 (in seconds)* Paper Capacity Standard: 650 sheets/Maximum: 2,300 sheets System (letter/legal/statement/envelope/label size). Optional: 550-sheet paper drawer and 100-sheet bypass tray (letter/legal/statement/envelope/label size). Paper Weights and Types Standard paper drawer and bypass tray: 16 lb. to 47 lb. bond (Plain paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Environmental Standards Power 100-127V AC, 47 to 63 Hz Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Output Size | Min. 5½" x 8½", Max. 8½" x 14" |
| Paper Capacity Paper Capacity Standard: 650 sheets/Maximum: 2,300 sheets Standard: 550-sheet paper drawer and 100-sheet bypass tray (letter/legal/statement/envelope/label size). Optional: 550-sheet paper drawer (letter/legal/statement/envelope/label size). Paper Weights And Types Paper Weights Standard paper drawer and bypass tray: 16 lb. to 47 lb. bond (Plain paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Account Control Supports user-number authentication Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Print Speed | 50 ppm |
| Paper Capacity Paper Feed Standard: 550-sheet paper drawer and 100-sheet bypass tray (letter/legal/statement/envelope/label size). Optional: 550- sheet paper drawer (letter/legal/statement/envelope/ label size). Paper Weights And Types Paper Weights Standard paper drawer and bypass tray: 16 lb. to 47 lb. bond (Plain paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Puplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Account Control Supports user-number authentication Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Envergy STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | First Print Time | Color: 5.5/Monochrome: 5.0 |
| Paper Feed Standard: 550-sheet paper drawer and 100-sheet bypass tray (letter/legal/statement/envelope/label size). Optional: 550- sheet paper drawer (letter/legal/statement/envelope/ label size). Paper Weights and Types Clain paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Envergy STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | (in seconds)* | |
| (letter/legal/statement/envelope/label size). Optional: 550-sheet paper drawer (letter/legal/statement/envelope/label size). Paper Weights and Types Claim paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Account Control Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Accessibility Features Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Paper Capacity | Standard: 650 sheets/Maximum: 2,300 sheets |
| (letter/legal/statement/envelope/label size). Optional: 550-sheet paper drawer (letter/legal/statement/envelope/label size). Paper Weights and Types Claim paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Account Control Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Accessibility Features Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Paper Feed | Standard: 550-sheet paper drawer and 100-sheet bypass tray |
| (Plain paper), Other paper types include pre-printed, recycled, pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1 GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Standards Power 100-127V AC, 47 to 63 Hz Exit Tray (Main): 300 sheets Capacity Power 0.86kW | System | (letter/legal/statement/envelope/label size). Optional: 550-sheet paper drawer (letter/legal/statement/envelope/ |
| pre-punched, letterhead, color paper, dual web labels, 16 to 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Paper Weights | Standard paper drawer and bypass tray: 16 lb. to 47 lb. bond |
| 28 lb. bond envelopes (up to 85 standard drawer, up to 10 bypass tray), integrated labels, paper labels, transparencies. Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | and Types | (Plain paper), Other paper types include pre-printed, recycled, |
| bypass tray), integrated labels, paper labels, transparencies. Duplexing Standard automatic duplex printing CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | - | pre-punched, letterhead, color paper, dual web labels, 16 to |
| CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Power 0.86kW | | 28 lb. bond envelopes (up to 85 standard drawer, up to 10 |
| CPU 1.2 GHz multi-processor design Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Power 0.86kW | | bypass tray), integrated labels, paper labels, transparencies. |
| RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Duplexing | |
| RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high speed ports, (front), wireless LAN optional (802.11 b/g/n) Printer Memory Standard: 1GB/Maximum: 3 GB Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | CPU | 1.2 GHz multi-processor design |
| Printer Memory Printer Memory Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Interface | RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0: 2 host, high |
| Account Control Supports user-number authentication Firmware Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Printer Memory | |
| Firmware Management Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | | |
| Management firmware update 1 to N with SRDM (Sharp Remote Device Manager) Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | | • • • |
| Device Setup Web-based management/cloning with user/administrator level login Service/Functions Remote access to service logs and click counts Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Management | firmware update 1 to N with SRDM (Sharp Remote Device |
| Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Device Setup | Web-based management/cloning with user/administrator |
| Accessibility Section 508, support of shortcut keystrokes on printer's numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Service/Functions | Remote access to service logs and click counts |
| numeric keypad, raised operator panel keys, compress image up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Accessibility | |
| up to 2.8% to fit on screen Environmental ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Features | |
| Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | | up to 2.8% to fit on screen |
| Standards Power 100-127V AC, 47 to 63 Hz Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Environmental | ENERGY STAR Program Ver. 3.0, European RoHS, Blue Angel |
| Power 100-127V AC, 47 to 63 Hz Dutput Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Standards | - · · · · · · · · |
| Output Tray Exit Tray (Main): 300 sheets Capacity Power 0.86kW | Power | 100-127V AC, 47 to 63 Hz |
| Capacity Power 0.86kW | Output Tray | · |
| Power 0.86kW | Capacity | , |
| | Power | 0.86kW |
| | Consumtion | |

| Main Specifications (continued) | | |
|---------------------------------|--|--|
| Weight | Approx. 80.5 lbs. | |
| Dimensions | Approx. 18.7" (w) x 19.5" (d) x 16.4" (h) | |
| PDL | Standard PCL 6, PostScript 3 compatible | |
| Resolution | 1,200 x 1,200 dpi | |
| Print Drivers | Windows Server®2003, Windows 7, Windows 8.1, Windows | |
| | 10, Windows Server 2008, Windows Server 2012, W, MAC | |
| | OSX (including 10.10 to 10.15), UNIX, Linux | |
| Features | Duplex printing, driver delivery functions, toner save mode, | |
| | electronic sorting, fit-to-page mode | |
| Direct Printing | BMP, DCX, DOC/DOCX, GIF, JPEG, PCX, PDF, PNG, PPT/PPTX, | |
| File Types | TIFF, XLS/XLSX, XPS. Methods: FTP, SMB, Web page, Email | |
| | and USB memory | |
| Direct Print | FTP, USB memory and web page | |
| Methods | | |
| Resident Fonts | 89 outline fonts (PCL), 158 fonts (PS) | |
| Network Interface | RJ-45 Ethernet, 10/100 Base-TX, USB 2.0, wireless | |
| | 10Base-T, 100Base-T, 1000Base-T | |
| Operating Systems | | |
| | 10, Windows Server 2008, Windows Server 2012, MacOS X | |
| | (including 10.10 to 10.15), UNIX, Linux | |
| Network Protocols | TCP/IP (IPv4, IPv6, TCP X, UDP X, IPSEC w/ IPv4 X, IPSEC w/ | |
| | IPv6 X, ICMP X, IGMP X) | |
| Printing | LPR, IPP, Raw TCP (port 9100) and FTP | |
| Protocols | | |
| Network Security | Includes IP address filtering, data Security TLS encryption, | |
| | Kerberos, 3-times data overwrite with optional hard disk | |
| Mobile Printing | Airprint®, Android printing framework | |
| Ontional Environan | | |
| Optional Equipmen | | |
| MX-CS17 | 550-sheet Paper Feed Unit | |
| Supplies | | |
| MX-C51TB | Black Toner Cartridge | |
| MX-C51TC | Cyan Toner Cartridge | |
| MX-C51TM | Magenta Toner Cartridge | |
| MX-C51TY | Yellow Toner Cartridge | |
| MX-C50DU-B | Black Imaging Kit | |
| MX-C50DU-S | Color Imaging Kit | |
| 00000 0 | | |

^{*} May vary depending on product configuration, machine settings and operating and/or environmental conditions.











SHARP ELECTRONICS CORPORATION 100 Paragon Drive, Montvale, NJ 07645 1-800-BE-SHARP • www.sharpusa.com Sharp, Sharp OSA, Sharpdesk, My Sharp, and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Microsoft, Office 365, Windows, Windows Server, Excel, PowerPoint, OneDrive, and SharePoint are trademarks or registered trademarks of Microsoft Corporation. Android, Chrome, Gmail, Google Drive, Google Cloud Print, and Chromebook are trademarks or registered trademarks of Google LLC. Adobe, the Adobe logo, PostScript, and PostScript 3 are either registered trademarks or trademarks of Adobe in the United States and/or other countries. Design and specifications subject to change without notice.