



Toshiba e-Studio 5520c 6520c 6530c Colour Photocopier Systems



Datasheet



Colour Manager

- High volume output performance – in B&W and Full Colour.
- Seamless integration into your office, network and enterprise.
- Enhanced operability takes ease of use to a new level.
- Solid security for easy and intelligent control of your documents and information.

e-STUDIO5520c
e-STUDIO6520c
e-STUDIO6530c



Networking Documents.

TOSHIBA
Leading Innovation >>>



e-STUDIO5520c
e-STUDIO6520c
e-STUDIO6530c



General	Print & Copy Speed Warm-up Time Paper Size & Weight Paper Capacity Automatic Duplex Controller Type Memory Interface Dimensions & Weight	Colour: 55/65/65 ppm (A4), 27/30/30 ppm (A3) B&W: 55/65/75 ppm (A4), 27/30/37 ppm (A3) Approx. <70 seconds from low-power mode Cassettes: A5R-320 x 460 mm, 64-256 gsm Tandem LCF ²⁾ : A4, 64-256 gsm Bypass: A6R-13" x 19", 64-300 gsm, banner paper 313 x 1,200 mm, 64-256 gsm 4 x 540 sheets (Cassettes) or 2 x 540 sheets (Cassettes) + 2,320 sheets (Tandem LCF) ²⁾ , 100 sheets (Bypass) Maximum: 6,000 ²⁾ sheets with external LCF ¹⁾ Up to 320 x 460 mm and 256 gsm Toshiba e-BRIDGE 80 GB HDD, 2.0 GB RAM 10/100/1000BaseT (incl. IPv6), High-Speed USB 2.0, WLAN ¹⁾ (IEEE802.11b/g), Bluetooth ¹⁾ 980 x 698 x 1,540 mm (W x D x H), ~ 246 kg
Print	Resolution Page Description Language Supported Systems Colour Modes Colour Settings	Max. 600 x 600 dpi, 8 bit per channel Max. 1,200 x 1,200 dpi, 2 bit per channel ³⁾ XPS, PCL6 and PostScript 3 compatible Windows 2000, Windows XP/Server2003/Server 2008/Vista (32/64 bit), Mac OS X, Linux/UNIX, Novel Netware (NDPS), Citrix, SAP, AS/400 Auto-Colour (ACS), Colour, Grayscale, B&W Brightness, Saturation, Contrast, Colour Balance
Scan	Resolution Scan Speed Document Feeder Scan Modes File Formats Scan Functions	Max. 600 x 600 dpi, 8 bit per channel Colour & B&W: Up to 77 pages/min. (300 dpi) Max. 100 sheets, A5R-A3, 35-209 gsm Auto-Colour (ACS), Colour, Grayscale, B&W JPEG, Multi/Single Page TIFF, Multi/Single Page XPS, Multi/Single Page PDF, Secure PDF, Slim PDF (high compression), Searchable PDF ¹⁾ (and other editable formats like DOC, XLS, RTF, TXT) ¹⁾ WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP), Meta Scan ¹⁾ , Scan to Box (e-Filing), TWAIN 1.7
Copy	Resolution First Copy Zoom Copy Modes Colour Modes Colour Settings	Scanning: 600 x 600 dpi, 10 bit per channel Printing: 600 x 600 dpi, 8 bit per channel 2,400 x 600 dpi, B&W with smoothing Colour: Approx. 6.5 seconds B&W: Approx. 5.3/5.3/4.6 seconds 25-400% (platen glass), 25-200% (RADF) Text, Text/Photo, Photo, Printed Image, Map Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&W Hue, Saturation, Colour Balance, 5 One-touch Modes, RGB Adjustment
Fax¹⁾	Communication Transmission Speed Compression Network-Fax Incoming Fax Routing	Super G3, G3 - (opt. 2 nd line), Internet Fax T.37 Approx. 3 seconds per page JBIG, MMR, MR, MH Driver for Windows 2000/XP/Vista (32/64 bit) To shared folder (SMB, FTP), e-mail, e-Filing
System & Security	Device Management System Features Accounting & Security	e-BRIDGE Fleet Management Software ¹⁾ , TopAccess remote administration & configuration e-Filing document server for secure storage, document distribution and Print-on-Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan preview, Print from USB, e-BRIDGE Open Platform ¹⁾ Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, card reader support, private print, standard data encryption, Data Overwrite Kit ¹⁾ , IP and MAC address filter, port filter, support of SSL and IPsec ¹⁾ protocol, IEEE802.1x support, Scan to secure PDF Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 gsm if not otherwise mentioned.

OPTIONS

MULTI-STAPLE FINISHER – MJ-1103

2 trays, 3,250 sheet capacity
 50 sheet multi-position stapling
 A5R-A3, 64-105 gsm (staple mode)
 617 x 603 x 1,085 mm (W x D x H), ~ 40 kg

SADDLE-STITCH FINISHER – MJ-1104

2 trays, 3,250 sheet capacity
 50 sheet multi-position stapling
 Saddle-stitched booklets of up to 60 pages
 A5R-A3, 64-105 gsm (staple mode)
 617 x 603 x 1,085 mm (W x D x H), ~ 70 kg

HOLE PUNCH UNIT – MJ-6102

Option for Finisher MJ-1103/MJ-1104
 Available in 2-holes (E), 4-holes (F),
 112 x 573 x 323 mm (W x D x H), ~ 7 kg

LARGE CAPACITY FEEDER – MP-2501A

2,500 sheet capacity, A4, 64-256 gsm
 360 x 552 x 542 mm (W x D x H), ~ 29 kg

OTHER OPTIONS

FAX BOARD GD-1270EU
 DATA OVERWRITE KIT GP-1070
 E-BRIDGE ID-GATE KP-2004/KP-2005
 IMAGING ACCELERATION BOARD GE-1170
 WIRELESS LAN ADAPTER GN-1050
 BLUETOOTH ADAPTER GN-2010
 META SCAN ENABLER GS-1010
 WEB-SERVICES ENABLER GS-1020

- ¹⁾ Optional
²⁾ e-STUDIO5520c tandem LCF version only
³⁾ PostScript driver only

TOSHIBA TEC UK
IMAGING SYSTEMS LTD

ABBEY CLOISTERS, ABBEY GREEN,
 CHERTSEY, SURREY, KT16 8RB.
 TEL 01932 580100 FAX 01932 580101
 WWW.TOSHIBA.CO.UK/IMAGING



Printed on 50% recycled / 50% FSC virgin fibre. www.fsc.org

Leasing Options in London

020 7635-5252

TOSHIBA
 Leading Innovation >>>

6BY0COP1547

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this document. D56530cGB0808